


Smart-Joint - Butt Fusion

Butt Fusion Elbow 45°



Raw Material:PE4710

Standard:ASTM D2513; ASTM D3261 D3035 D3350 AWWA C901

Followed parameters are for reference.

Code	SizeΦ(mm)	SDR	Pcs/Box	L	L1
IBFL41E/A	1" IPS×45°	9/11	90	90	67
IBFL411/4E/A	1 1/4" IPS×45°	9/11	85	93	67
IBFL411/2E/A	1 1/2" IPS×45°	9/11	80	95	67
IBFL42E/A	2" IPS×45°	9/11	45	113	72
IBFL43E/A	3" IPS×45°	9/11	30	125	80
IBFL44E/A	4" IPS×45°	9/11	20	137	84
IBFL46E/A	6" IPS×45°	9/11	12	174	108
IBFL48E/A	8" IPS×45°	9/11	4	225	152
IBFL410A/B	10" IPS×45°	11/17	1	220	140
IBFL412A/B	12" IPS×45°	11/17	1	244	150
IBFL414A/B	14" IPS×45°	11/17	1	260	165
IBFL416A/B	16" IPS×45°	11/17	1	254	130
IBFL418A/B	18" IPS×45°	11/17	1	263	130
IBFL420A/B	20" IPS×45°	11/17	1	273	130
IBFL21A/B	1" IPS×22.5°	9/11	90	67	38
IBFL22A/B	2" IPS×22.5°	9/11	50	108	72
IBFL23A/B	3" IPS×22.5°	9/11	25	115	80
BFL24A/B	4" IPS×22.5°	9/11	13	125	84
BFL26A/B	6" IPS×22.5°	9/11	4	155	108
BFL28A/B	8" IPS×22.5°	9/11	2	200	152.4
DBFL410A/B	10" DIPS×45°	11/17	1	232	140
DBFL412A/B	12" DIPS×45°	11/17	1	256	150