



Raw Material:PE4710

Standard:ASTM D2513; ASTM D3261 D3035 D3350 AWWA C901

Followed parameters are for reference.

Code	SizeΦ(mm)	SDR	Pcs/Box	L1	L2	L3	L
IBFT1E/A	1"-1"-1" IPS	9/11	60	67	67	98	67
IBFT11E/A	1 1/4"-1 1/4"-1 1/4" IPS	9/11	50	67	67	205	103
IBFT11/2E/A	1 1/2"-1 1/2"-1 1/2" IPS	9/11	40	67	67	106	211
IBFT2E/A	2"-2"-2" IPS	9/11	30	72	72	130	260
IBFT3E/A	3"-3"-3" IPS	9/11	12	80	80	155	310
IBFT4E/A	4"-4"-4" IPS	9/11	6	84	84	174	348
IBFT6E/A	6"-6"-6" IPS	9/11	3	108	108	228	456
IBFT8E/A	8"-8"-8" IPS	9/11	1	152.4	152.4	291	581
DBFT10A/B	10"-10"-10" DIPS	11/17	1	140	140	309	617
DBFT12A/B	12"-12"-12" DIPS	11/17	1	150	150	352	720
IBFT10A/B	10"-10"-10" IPS	11/17	1	140	140	320	660
IBFT12A/B	12"-12"-12" IPS	11/17	1	150	150	352	720
IBFT14A/B	14"-14"-14" IPS	11/17	1	165	165	384	766
IBFT16A/B	16"-16"-16" IPS	11/17	1	130	130	368	750
IBFT18A/B	18"-18"-18" IPS	11/17	1	130	130	392	800
IBFT20A/B	20"-20"-20" IPS	11/17	1	130	130	428	855
IBFT32E/A	3"-2"-3"IPS	9/11	12	72	72	144	310
IBFT42E/A	4"-2"-4"IPS	9/11	7	72	72	157	348
IBFT64E/A	6"-4"-6"IPS	9/11	4	84	84	203	456
IBFT84E/A	8"-4"-8"IPS	9/11	1	84	84	227	581