


# Smart-Joint - Butt Fusion




## Butt Fusion Tee



Raw Material:PE100 PE100RC PERTII  
 Standard:ISO4437-3 ISO4427-3 EN12201-3 ISO22391-3  
 SDR9 can be supplied per request.  
 Followed parameters are for reference.

Code	SizeΦ(mm)	SDR	Pcs/Box	L1	L2	L3	L
BFT7540A	75-40	11	25	68	70	113	220
BFT7550A	75-50	11	25	68	70	108	220
BFT7563A	75-63	11	24	67	70	107	220
BFT9040A/B	90-40	11/17	18	56	80	112	250
BFT9050A/B	90-50	11/17	18	69	80	118	250
BFT9063A/B	90-63	11/17	18	69	80	116	250
BFT9075A/B	90-75	11/17	12	78	79	138	278
BFT11032A	110-32	11	12	57	82	129	255
BFT11040A/B	110-40	11/17	12	53	82	126	259
BFT11050A/B	110-50	11/17	12	59	82	130	259
BFT11063A/B	110-63	11/17	12	68	83	135	259
BFT11075A/B	110-75	11/17	12	78	83	150	303
BFT11090A/B	110-90	11/17	12	78	83	150	303
BFT12563A	125-63	11	9	64	88	142	288
BFT12575A	125-75	11	9	70	88	149	288
BFT12590A/B	125-90	11/17	7	85	86	162	323
BFT125110A/B	125-110	11/17	7	85	87	161	335
BFT14063A	140-63	11	7	65	94	149	300
BFT14075A	140-75	11	7	74	94	161	298
BFT14090A	140-90	11	5	82	92	124	330
BFT140110A	140-110	11	5	84	93	166	334
BFT140125A/B	140-125	11/17	5	86	92	188	383
BFT16063A/B	160-63	11/17	5	62	99	152	300
BFT16090A/B	160-90	11/17	4	84	98	175	353
BFT160110A/B	160-110	11/17	4	81	98	182	353
BFT18063A	180-63	11	4	69	107	183	358
BFT18075A	180-75	11	4	74	107	195	359
BFT18090A	180-90	11	2	82	105	190	353




Raw Material:PE100 PE100RC PERTII  
 Standard:ISO4437-3 ISO4427-3 EN12201-3 ISO22391-3  
 SDR9 can be supplied per request.  
 Followed parameters are for reference.

Code	SizeΦ(mm)	SDR	Pcs/Box	L1	L2	L3	L
BFT180110A	180-110	11	2	85	106	190	354
BFT180125A	180-125	11	2	89	107	194	395
BFT180140A	180-140	11	2	92	106	201	395
BFT180160A	180-160	11	2	95	105	224	457
BFT20063A/B	200-63	11/17	2	81	112	196	366
BFT20090A/B	200-90	11/17	2	81	112	196	366
BFT200110A/B	200-110	11/17	2	81	112	196	367
BFT200160A/B	200-160	11/17	2	97	119	230	429
BFT22590A	225-90	11	1	84	122	215	401
BFT225110A	225-110	11	1	85	122	216	403
BFT225125A	225-125	11	1	90	123	222	414
BFT225140A	225-140	11	1	95	122	222	415
BFT225160A/B	225-160	11/17	1	99	121	220	438
BFT250110A/B	250-110	11/17	1	81	129	220	403
BFT250160A/B	250-160	11/17	1	102	129	257	472
BFT280125A	280-125	11	1	92	142	407	504
BFT280140A	280-140	11	1	96	142	412	504
BFT280160A	280-160	11	1	103	142	410	504
BFT315110A/B*	315-110	11/17	1	85/95	150/90	280/275	525/280
BFT315125A/B	315-125	11/17	1	92	151	443	528
BFT315140A/B	315-140	11/17	1	96	151	443	528
BFT315160A/B	315-160	11/17	1	101	151	453	528
BFT315200A/B	315-200	11/17	1	118	152	310	695
BFT315250A/B	315-250	11/17	1	134	151	320	694
BFT315280A/B	315-280	11/17	1	135	160	325	680
BFT355200A*/B	355-200	11/17	1	100/149	90/197	287/352	400/646
BFT355250A*/B	355-250	11/17	1	100/164	90/166	287/368	450/634

# Smart-Joint - Butt Fusion



## Butt Fusion Tee



Raw Material:PE100 PE100RC PERTII  
 Standard:ISO4437-3 ISO4427-3 EN12201-3 ISO22391-3  
 SDR9 can be supplied per request.  
 Followed parameters are for reference.

Code	SizeΦ(mm)	SDR	Pcs/Package	L1	L2	L3	L
BFT400200A*/B	400-200	11/17	18	100/138	110/176	360	450/594
BFT400250A*/B	400-250	11/17	18	100/126	110/138	360	490/594
BFT400315A*/B	400-315	11/17	18	100/125	110/94	358	555/597
BFT450355A*/B	450-355	11/17	10	100/150	110/123	423	595/597
BFT450250A/B	450-250	11/17	10	150	123	423	597
BFT450355A/B	450-355	11/17	8	150	123	423	723
BFT500160A/B	500-160	11/17	8	131	130	425	530
BFT500250A/B	500-250	11/17	8	130	130	445	620
BFT500355A/B	500-355	11/17	8	130	130	415	716
BFT630200A/B	630-200	11/17	2	132	128	520	576
BFT630250A/B	630-250	11/17	2	133	130	470	620
BFT630280B	630-280	17	2	133	128	515	628
BFT630315A/B	630-315	11/17	2	131	131	525	783
BFT630400A/B	630-400	11/17	2	130	135	480	775
BFT5040A	50-40	11	80	50	54	85	179
BFT6332A	63-32	11	50	50	63	93	200
BFT6340A	63-40	11	50	53	56	88	186
BFT6350A	63-50	11	50	63	64	126	224

